



Bearing No. JHM33449/JHM33410

e	0.35
d	24 mm
D	55 mm
T	25 mm
B	25 mm
C	21 mm
a	15,8 mm
Da	47 mm
B_	25
Db	52 mm
da	35 mm
Y0	0.93
db	30 mm
C0	55
D_	55
Z_	13
C_	21
Y1	1.7
DE_	46.678
SLR	17.5
D_a	47
DI_	17.431
DA1	8.028
DA2	6.76
CUP	0.107
DA_	7.397
D_b	52
RAr	110.417
SDM_	39.378
KBRG	3141

yobi	JHM33449/JHM33410
CONE	0.181
ALP21	26
ALP22	30
ALP23	0
BETA_	2
BET21	4
BET23	0
BET22	10
r min.	2 mm
LangID	1
Weight	0,288 Kg
ALPHA_	13.25
r1 min.	2 mm
ra max.	2 mm
Oil rpm	9500
outer r	2
hidYobi	JHM33449/JHM33410
GRS rpm	7100
inner r	2
hidTable	ecat_NSTPRI
inner ra	2
outer rb	2
ra1 max.	2 mm
Size (mm)	24x55x25
SHOG_yobi	JHM33449R/JHM33410 R
Prod_Type3	TRBSR_ID_A
Width (mm)	25
Bearing number	JHM33449/JHM33410
Bore Diameter (mm)	24
Outer Diameter (mm)	55
Calculation factor (e)	0,35

(Oil) Lubrication Speed	9500 r/min
Calculation factor (Y0)	0,93
(Grease) Lubrication Speed	7100 r/min
Basic static load rating (C0)	55 kN
Basic dynamic load rating (C)	49,5 kN