



## Bearing No. 53316

R	112 mm
C	164
r	1.5
d	80 mm
D	140 mm
T	47,6 mm
A	50 mm
R_	112
B_	47.6
ra	1.5
C0	395
da	116
Z_	15
A_	50
T3	47.6
d1	140 mm
D_	140
D1	82 mm
D_1	82
DA_	20.638
SRI	11.15
SRE	11.15
D_a	104
SREN	0
SRIN	0
yobi	53316
SRIX	0.05
mass	2.94
SDM_	110
KBRG	5121

SREX	0.05
Noun	Bearing
Height	1.89 Inch   48 Millimeter
Bore 2	3.228 Inch   82 Millimeter
Banded	No
UNSPSC	31171552
r min.	1,5 mm
LangID	1
Weight	2,94 Kg
Bore 1	3.15 Inch   80 Millimeter
GRS rpm	1300
hidYobi	53316
Oil rpm	1900
ra max.	1,5 mm
Da max.	104 mm
da min.	116 mm
Category	Thrust Ball Bearings
hidTable	ecat_NSSDTB
Size (mm)	80x140x47.6
Inventory	0.0
Prod_Type3	TB_SD_WAS
Width (mm)	47,6
Weight / LBS	6.48159
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Bearing number	53316
Other Features	Single Row   With Aligning Seat
Thrust Bearing	Yes
Keyword String	Ball Thrust
Rolling Element	Ball Bearing

Precision Class	Non-Precision
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Long Description	80MM Bore 1; 82MM Bore 2; 140MM Outside Diameter; 48MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; Non-Precision
Outside Diameter	5.512 Inch   140 Millimeter
Weight / Kilogram	3.43
Manufacturer Name	NSK
Bore Diameter (mm)	80
Outer Diameter (mm)	140
Minimum Buy Quantity	N/A
Component Description	Roller Assembly Plus Raceways
Harmonized Tariff Code	8482.10.50.08
(Grease) Lubrication Speed	1300 r/min
Single or Double Direction	Single Direction
Basic static load rating (C0)	395 kN
Basic dynamic load rating (C)	164 kN
Overall Height with Aligning Washer	0 Inch   0 Millimeter