



Bearing No. 53316U

| | |
|-----------|-------------|
| R | 112 mm |
| T | 52 |
| d | 80 mm |
| D | 140 mm |
| A | 50 mm |
| C | 15 mm |
| Cu | 15.8 |
| Ca | 200 |
| T1 | 47,6 mm |
| T2 | 52 mm |
| d1 | 140 mm |
| D1 | 82 mm |
| D2 | 110 mm |
| D3 | 145 mm |
| Coa | 368 |
| r(min) | 1.5 |
| Weight | 3,43 Kg |
| r min. | 1,5 mm |
| da min. | 116 mm |
| Da max. | 104 mm |
| ra max. | 1,5 mm |
| da(min) | 116 |
| D3(min) | 145 |
| D2(min) | 110 |
| D1(min) | 82 |
| Da(max) | 104 |
| ra(max) | 1.5 |
| d1(max) | 140 |
| Oil lub. | 1800 |
| Size (mm) | 80x140x47.6 |

| | |
|-------------------------------|------------|
| Width (mm) | 47,6 |
| Bearing No. | 53316U |
| Grease lub. | 1200 |
| Bearing number | 53316U |
| (Refer.)Mass(kg) | 3.43 |
| Bore Diameter (mm) | 80 |
| Outer Diameter (mm) | 140 |
| (Grease) Lubrication Speed | 1200 r/min |
| Basic static load rating (C0) | 368 kN |
| Basic dynamic load rating (C) | 160 kN |