




Bearing No. NUP230EM

r	3
D	270 mm
C	45 mm
S	1,5 mm
B	45 mm
d	150 mm
Fw	182 mm
Z_	19
r1	3
da	163
C0	595
ra	2.5
rb	2.5
B_	45
D_	270
DA_	30
DE_	242
DI_	182
yobi	NUP230EM
mass	12.1
SDM_	212
KBRG	4165
SBRG	2
db min	163 mm
C_conv	450000
Db max	257 mm
r min.	3 mm
ALPHA_	0
LangID	1
dd min	196

dc min	184
Weight	11,9 Kg
db max	177
da min.	163 mm
D_a max	257
r1 min.	3 mm
rb max.	2,5 mm
TSR rpm	2800
Da max.	257 mm
GRS rpm	2200
Oil rpm	2800
ra max.	2,5 mm
hidYobi	NUP230EM
db max.	177 mm
hidTable	ecat_NSCLDR
Macha rpm	4300
Size (mm)	150x270x45
Prod_Type3	CRB_SR_NUP
Width (mm)	45
Bearing number	NUP230EM
Bore Diameter (mm)	150
Outer Diameter (mm)	270
(Grease) Lubrication Speed	2200 r/min
Basic static load rating (C0)	595 kN
Basic dynamic load rating (C)	450 kN