




Bearing No. 6006ZZE

D	55 mm
d	30 mm
B	13 mm
C	13 mm
Noun	Bearing
Bore	1.181 Inch 30 Millimeter
Width	13 mm
UNSPSC	31171504
r min.	1.0 mm
Weight	0.117 Kg
da min.	35 mm
Da max.	50 mm
ra max.	1.0 mm
Category	Single Row Ball Bearing
ra (max)	1 mm
da (min)	35 mm
Da (max)	50 mm
Bore Size	30 mm
Factor fo	14.8
Inventory	0.0
Bore Type	Cylindrical Bore
Enclosure	2 Metal Shields
Snap Ring	No
Size (mm)	30x55x13
Width (mm)	13
Inch - Metric	Metric
Configuration	Single Row
Product Group	B00308
Cage Material	Steel

Keyword String	Ball
Other Features	Deep Groove
Bearing number	6006ZZE
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	30MM Bore; 55MM Outside Diameter; 13MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Inner Race Width	0 Inch 0 Millimeter
Radial Clearance	0.005 to 0.020 mm
Outside Diameter	2.165 Inch 55 Millimeter
Manufacturer URL	http://www.nachiamerica.com
Outer Race Width	0.512 Inch 13 Millimeter
Manufacturer Name	NACHI
Weight / Kilogram	0
Internal Clearance	C0-Medium
Static Load Rating	8,300 N
Bore Diameter (mm)	30
Dynamic Load Rating	13,200 N
Outer Diameter (mm)	55
Minimum Buy Quantity	N/A
Fillet Radius/Chamfer	1 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	13,000 rpm
Internal Special Features	No

(Grease) Lubrication Speed	12000 r/min
Basic static load rating (C0)	8,3 kN
Basic dynamic load rating (C)	13,2 kN
Maximum Capacity / Filling Slot	No