



Bearing No. 30217CA

D	150 mm
d	85 mm
T	30,5 mm
B	28 mm
C	22 mm
a	36,2 mm
e	0.58
Cr	17500
Y0	0.57
db	98
da	100
Y1	1
B_	28
Sb	8.5
C0	226
Sa	5
D_	150
Z_	21
C_	22
C0r	23000
DA_	16.134
Iso	-
DE_	132.677
D_b	142
DI_	101.848
SBRG	2
SDM_	117.263
D_a2	131
KBRG	3111
yobi	30217CA

D_a1	140
mass	2.07
TC-RA	194.867
r min.	2,5 mm
Weight	2,07 Kg
TC-DA1	16.998
TC-DA2	15.27
TC-SLR	20
Da min	131 mm
LangID	1
ALPHA_	21
Db min.	142 mm
Oil rpm	3200
db max.	98 mm
Da max.	140 mm
ra max.	2 mm
hidYobi	30217CA
da min.	100 mm
T-ALP21	42
rb max.	2 mm
T-ALP22	0
T-ALP23	0
GRS rpm	2200
inner r	2.5
outer r	2
r1 min.	2 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	5
inner ra	2
outer rb	2
TC-BET22	0

Size (mm)	85x150x30.5
Width (mm)	30,5
Prod_Type3	TRBSR_MD_A
Bearing number	30217CA
Bore Diameter (mm)	85
Outer Diameter (mm)	150
Calculation factor (e)	0,58
Calculation factor (Y0)	0,57
(Oil) Lubrication Speed	3200 r/min
(Grease) Lubrication Speed	2200 r/min
Basic dynamic load rating (C)	171 kN
Basic static load rating (C0)	226 kN