



Bearing No. SYK 25 TR

N	17,5 mm
d	25 mm
A	32 mm
B	34,1 mm
G	10 mm
H	70,5 mm
J	105 mm
L	134 mm
N1	12 mm
s1	19,8 mm
A1	22 mm
H1	36,5 mm
H2	16 mm
J max.	110 mm
J min.	100 mm
Weight	0,29 Kg
Category	Mounted Units & Inserts
Inventory	0.0
N ₁	12.5 mm
A ₁	22 mm
s ₁	19.8 mm
H ₂	16 mm
H ₁	36.5 mm
B ₄	5 mm
Product Group	M06110
A ₅	18 mm
Bearing number	SYK 25 TR
Limiting speed	4300 r/min
Housing material	Composite
Weight / Kilogram	0.354

Manufacturer Name	SKF
Mass bearing unit	0.29 kg
Bore Diameter (mm)	25
Minimum Buy Quantity	N/A
Fatigue load limit (Pu)	0,335
Basic dynamic load rating C	14 kN
Basic static load rating (C0)	7,8 kN
Basic dynamic load rating (C)	14 kN
Thread grub screw G ₂	M6x0.75
Fatigue load limit P _u	0.335 kN
Hexagonal key size for grub screw N	3 mm
Basic static load rating C ₀	7.8 kN
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in