



### Bearing No. 53413

R	112 mm
C	234
r	2
d	65 mm
D	140 mm
T	60,2 mm
A	40 mm
R_	112
B_	60.2
ra	2
C0	495
da	110
Z_	11
A_	40
T3	60.2
d1	140 mm
D_	140
D1	68 mm
D_1	68
DA_	26.988
SRI	14.5
SRE	14.5
D_a	95
SREN	0
SRIN	0
yobi	53413
SRIX	0.1
mass	4.22
SDM_	102.5
KBRG	5121

SREX	0.1
Noun	Bearing
Bore 1	2.559 Inch   65 Millimeter
Weight	4,22 Kg
Banded	No
UNSPSC	31171552
r min.	2 mm
LangID	1
Bore 2	2.677 Inch   68 Millimeter
Height	2.37 Inch   60.2 Millimeter
GRS rpm	1100
hidYobi	53413
Oil rpm	1700
ra max.	2 mm
Da max.	95 mm
da min.	110 mm
Category	Thrust Ball Bearings
hidTable	ecat_NSSDTB
Size (mm)	65x140x60.2
Inventory	0.0
Prod_Type3	TB_SD_WAS
Width (mm)	60,2
Weight / LBS	9.30351
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Bearing number	53413
Other Features	Single Row   With Aligning Seat
Thrust Bearing	Yes

Keyword String	Ball Thrust
Rolling Element	Ball Bearing
Precision Class	Non-Precision
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Long Description	65MM Bore 1; 68MM Bore 2; 140MM Outside Diameter; 60.2MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; Non-Precision
Outside Diameter	5.512 Inch   140 Millimeter
Weight / Kilogram	5.28
Manufacturer Name	NSK
Bore Diameter (mm)	65
Outer Diameter (mm)	140
Minimum Buy Quantity	N/A
Component Description	Roller Assembly Plus Raceways
Harmonized Tariff Code	8482.10.50.08
(Grease) Lubrication Speed	1100 r/min
Single or Double Direction	Single Direction
Basic static load rating (C0)	495 kN
Basic dynamic load rating (C)	234 kN
Overall Height with Aligning Washer	0 Inch   0 Millimeter