



Bearing No. HR32938J

D	260 mm
d	190 mm
T	45 mm
B	45 mm
C	34 mm
a	55,3 mm
e	0.48
Cr	37000
Y0	0.69
db	201
da	205
Y1	1.3
B_	45
Sb	11
C0	715
Sa	8
D_	260
Z_	36
C_	34
C0r	73000
DA_	16.661
Iso	4DC
DE_	239.396
D_b	251
DI_	207.422
SBRG	29
SDM_	223.409
D_a2	237
KBRG	3111
yobi	HR32938J

D_a1	250
mass	6.83
TC-RA	411
r min.	2,5 mm
Weight	6,83 Kg
TC-DA1	17.334
TC-DA2	15.988
TC-SLR	32
Da min	237 mm
LangID	1
ALPHA_	17.65
Db min.	251 mm
Oil rpm	1600
db max.	201 mm
Da max.	250 mm
ra max.	2 mm
hidYobi	HR32938J
da min.	205 mm
T-ALP21	35
rb max.	2 mm
T-ALP22	18
T-ALP23	0
GRS rpm	1200
inner r	2.5
outer r	2
r1 min.	2 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	2
inner ra	2
outer rb	2
TC-BET22	25

Size (mm)	190x260x45
Width (mm)	45
Prod_Type3	TRBSR_MD_A
Bearing number	HR32938J
Bore Diameter (mm)	190
Outer Diameter (mm)	260
Calculation factor (e)	0,48
Calculation factor (Y0)	0,69
(Oil) Lubrication Speed	1600 r/min
(Grease) Lubrication Speed	1200 r/min
Basic dynamic load rating (C)	365 kN
Basic static load rating (C0)	715 kN