



Bearing No. HR32321J

D	225 mm
d	105 mm
T	81,5 mm
B	77 mm
C	63 mm
a	55,2 mm
e	0.35
Cr	68000
Y0	0.96
db	129
da	130
Y1	1.7
B_	77
Sb	18.5
C0	925
Sa	6
D_	225
Z_	16
C_	63
C0r	94500
DA_	30.288
Iso	2GD
DE_	193.849
D_b	209
DI_	134.918
SBRG	23
SDM_	164.384
D_a2	186
KBRG	3111
yobi	HR32321J

D_a1	211
mass	14.9
TC-RA	462.321
r min.	4 mm
Weight	14,9 Kg
TC-DA1	32.267
TC-DA2	28.308
TC-SLR	57
Da min	186 mm
LangID	1
ALPHA_	12.953
Db min.	209 mm
Oil rpm	2200
db max.	129 mm
Da max.	211 mm
ra max.	3 mm
hidYobi	HR32321J
da min.	130 mm
T-ALP21	25
rb max.	2,5 mm
T-ALP22	54
T-ALP23	20
GRS rpm	1700
inner r	4
outer r	3
r1 min.	3 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	4
inner ra	3
outer rb	2.5
TC-BET22	0

Size (mm)	105x225x81.5
Width (mm)	81,5
Prod_Type3	TRBSR_MD_A
Bearing number	HR32321J
Bore Diameter (mm)	105
Outer Diameter (mm)	225
Calculation factor (e)	0,35
Calculation factor (Y0)	0,96
(Oil) Lubrication Speed	2200 r/min
(Grease) Lubrication Speed	1700 r/min
Basic dynamic load rating (C)	670 kN
Basic static load rating (C0)	925 kN