



Bearing No. HR32913J

D	90 mm
d	65 mm
T	17 mm
B	17 mm
C	14 mm
a	16,8 mm
e	0.35
Cr	5000
Y0	0.93
db	70
da	74
Y1	1.7
B_	17
Sb	3
C0	86.5
Sa	4
D_	90
Z_	38
C_	14
C0r	8800
DA_	5.218
Iso	2BC
DE_	82.146
D_b	86
DI_	71.975
SBRG	29
SDM_	77.061
D_a2	82
KBRG	3111
yobi	HR32913J

D_a1	84
mass	0.323
TC-RA	185.267
r min.	1 mm
Weight	0,323 Kg
TC-DA1	5.389
TC-DA2	5.046
TC-SLR	11.8
Da min	82 mm
LangID	1
ALPHA_	13.25
Db min.	86 mm
Oil rpm	5000
db max.	70 mm
Da max.	84 mm
ra max.	1 mm
hidYobi	HR32913J
da min.	74 mm
T-ALP21	26
rb max.	1 mm
T-ALP22	30
T-ALP23	0
GRS rpm	3600
inner r	1
outer r	1
r1 min.	1 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	1
inner ra	1
outer rb	1
TC-BET22	40

Size (mm)	65x90x17
Width (mm)	17
Prod_Type3	TRBSR_MD_A
Bearing number	HR32913J
Bore Diameter (mm)	65
Outer Diameter (mm)	90
Calculation factor (e)	0,35
Calculation factor (Y0)	0,93
(Oil) Lubrication Speed	5000 r/min
(Grease) Lubrication Speed	3600 r/min
Basic dynamic load rating (C)	49 kN
Basic static load rating (C0)	86,5 kN