



Bearing No. HR32922J

D	150 mm
d	110 mm
T	25 mm
B	25 mm
C	20 mm
a	26,5 mm
e	0.36
Cr	12500
Y0	0.93
db	119
da	121
Y1	1.7
B_	25
Sb	5
C0	224
Sa	5
D_	150
Z_	37
C_	20
C0r	22800
DA_	9.263
Iso	2CC
DE_	139.922
D_b	145
DI_	121.736
SBRG	29
SDM_	130.829
D_a2	142
KBRG	3111
yobi	HR32922J

D_a1	142
mass	1.29
TC-RA	312
r min.	1,5 mm
Weight	1,29 Kg
TC-DA1	9.529
TC-DA2	8.996
TC-SLR	17.5
Da min	142 mm
LangID	1
ALPHA_	13.333
Db min.	145 mm
Oil rpm	2800
db max.	119 mm
Da max.	142 mm
ra max.	1,5 mm
hidYobi	HR32922J
da min.	121 mm
T-ALP21	26
rb max.	1,5 mm
T-ALP22	40
T-ALP23	0
GRS rpm	2200
inner r	1.5
outer r	1.5
r1 min.	1,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	1
inner ra	1.5
outer rb	1.5
TC-BET22	45

Size (mm)	110x150x25
Width (mm)	25
Prod_Type3	TRBSR_MD_A
Bearing number	HR32922J
Bore Diameter (mm)	110
Outer Diameter (mm)	150
Calculation factor (e)	0,36
Calculation factor (Y0)	0,93
(Oil) Lubrication Speed	2800 r/min
(Grease) Lubrication Speed	2200 r/min
Basic dynamic load rating (C)	123 kN
Basic static load rating (C0)	224 kN