



Bearing No. HR32305J

D	62 mm
d	25 mm
T	25,25 mm
B	24 mm
C	20 mm
a	15,6 mm
e	0.3
Cr	6400
Y0	1.1
db	32
da	38
Y1	2
B_	24
Sb	5
C0	66
Sa	3
D_	62
Z_	13
C_	20
C0r	6750
DA_	9.393
Iso	2FD
DE_	52.637
D_b	57
DI_	34.219
SBRG	23
SDM_	43.428
D_a2	51
KBRG	3111
yobi	HR32305J

D_a1	53
mass	0.376
TC-RA	143.039
r min.	1,5 mm
Weight	0,376 Kg
TC-DA1	9.983
TC-DA2	8.803
TC-SLR	17
Da min	51 mm
LangID	1
ALPHA_	11.31
Db min.	57 mm
Oil rpm	8500
db max.	32 mm
Da max.	53 mm
ra max.	1,5 mm
hidYobi	HR32305J
da min.	38 mm
T-ALP21	22
rb max.	1,5 mm
T-ALP22	37
T-ALP23	12
GRS rpm	6300
inner r	1.5
outer r	1.5
r1 min.	1,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	4
inner ra	1.5
outer rb	1.5
TC-BET22	0

Size (mm)	25x62x25.25
Width (mm)	25,25
Prod_Type3	TRBSR_MD_A
Bearing number	HR32305J
Bore Diameter (mm)	25
Outer Diameter (mm)	62
Calculation factor (e)	0,3
Calculation factor (Y0)	1,1
(Oil) Lubrication Speed	8500 r/min
(Grease) Lubrication Speed	6300 r/min
Basic dynamic load rating (C)	62,5 kN
Basic static load rating (C0)	66 kN