



Bearing No. HR32308J

D	90 mm
d	40 mm
T	35,25 mm
B	33 mm
C	27 mm
a	23,4 mm
e	0.35
Cr	12200
Y0	0.96
db	50
da	54
Y1	1.7
B_	33
Sb	8
C0	145
Sa	3
D_	90
Z_	16
C_	27
C0r	14800
DA_	11.834
Iso	2FD
DE_	75.463
D_b	82
DI_	52.725
SBRG	23
SDM_	64.094
D_a2	73
KBRG	3111
yobi	HR32308J

D_a1	81
mass	1.05
TC-RA	181
r min.	2 mm
Weight	1,05 Kg
TC-DA1	12.633
TC-DA2	11.035
TC-SLR	23
Da min	73 mm
LangID	1
ALPHA_	12.953
Db min.	82 mm
Oil rpm	6000
db max.	50 mm
Da max.	81 mm
ra max.	2 mm
hidYobi	HR32308J
da min.	54 mm
T-ALP21	25
rb max.	1,5 mm
T-ALP22	54
T-ALP23	20
GRS rpm	4300
inner r	2
outer r	1.5
r1 min.	1,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	4
inner ra	2
outer rb	1.5
TC-BET22	0

Size (mm)	40x90x35.25
Width (mm)	35,25
Prod_Type3	TRBSR_MD_A
Bearing number	HR32308J
Bore Diameter (mm)	40
Outer Diameter (mm)	90
Calculation factor (e)	0,35
Calculation factor (Y0)	0,96
(Oil) Lubrication Speed	6000 r/min
(Grease) Lubrication Speed	4300 r/min
Basic dynamic load rating (C)	120 kN
Basic static load rating (C0)	145 kN