



Bearing No. HR32212J

D	110 mm
d	60 mm
T	29,75 mm
B	28 mm
C	24 mm
a	24,1 mm
e	0.41
Cr	13400
Y0	0.81
db	68
da	72
Y1	1.5
B_	28
Sb	5.5
C0	167
Sa	4
D_	110
Z_	19
C_	24
C0r	17000
DA_	12.89
Iso	3EC
DE_	96.716
D_b	104
DI_	71.11
SBRG	22
SDM_	83.913
D_a2	95
KBRG	3111
yobi	HR32212J

D_a1	101
mass	1.18
TC-RA	194.627
r min.	2 mm
Weight	1,18 Kg
TC-DA1	13.584
TC-DA2	12.196
TC-SLR	20
Da min	95 mm
LangID	1
ALPHA_	15.109
Db min.	104 mm
Oil rpm	4500
db max.	68 mm
Da max.	101 mm
ra max.	2 mm
hidYobi	HR32212J
da min.	72 mm
T-ALP21	30
rb max.	1,5 mm
T-ALP22	13
T-ALP23	8
GRS rpm	3400
inner r	2
outer r	1.5
r1 min.	1,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	4
inner ra	2
outer rb	1.5
TC-BET22	0

Size (mm)	60x110x29.75
Width (mm)	29,75
Prod_Type3	TRBSR_MD_A
Bearing number	HR32212J
Bore Diameter (mm)	60
Outer Diameter (mm)	110
Calculation factor (e)	0,41
Calculation factor (Y0)	0,81
(Oil) Lubrication Speed	4500 r/min
(Grease) Lubrication Speed	3400 r/min
Basic dynamic load rating (C)	131 kN
Basic static load rating (C0)	167 kN