



Bearing No. HR32228J

D	250 mm
d	140 mm
T	71,75 mm
B	68 mm
C	58 mm
a	60,5 mm
e	0.44
Cr	62000
Y0	0.76
db	159
da	161
Y1	1.4
B_	68
Sb	13.5
C0	915
Sa	9
D_	250
Z_	19
C_	58
C0r	93500
DA_	27.647
Iso	4FD
DE_	220.866
D_b	238
DI_	166.88
SBRG	22
SDM_	193.873
D_a2	213
KBRG	3111
yobi	HR32228J

D_a1	236
mass	14.3
TC-RA	421
r min.	4 mm
Weight	14,3 Kg
TC-DA1	29.383
TC-DA2	25.911
TC-SLR	50
Da min	213 mm
LangID	1
ALPHA_	16.173
Db min.	238 mm
Oil rpm	1900
db max.	159 mm
Da max.	236 mm
ra max.	3 mm
hidYobi	HR32228J
da min.	161 mm
T-ALP21	32
rb max.	2,5 mm
T-ALP22	20
T-ALP23	40
GRS rpm	1400
inner r	4
outer r	3
r1 min.	3 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	4
inner ra	3
outer rb	2.5
TC-BET22	0

Size (mm)	140x250x71.75
Width (mm)	71,75
Prod_Type3	TRBSR_MD_A
Bearing number	HR32228J
Bore Diameter (mm)	140
Outer Diameter (mm)	250
Calculation factor (e)	0,44
Calculation factor (Y0)	0,76
(Oil) Lubrication Speed	1900 r/min
(Grease) Lubrication Speed	1400 r/min
Basic dynamic load rating (C)	610 kN
Basic static load rating (C0)	915 kN