



Bearing No. HR32034XJ

D	260 mm
d	170 mm
T	57 mm
B	57 mm
C	43 mm
a	56,6 mm
e	0.44
Cr	51500
Y0	0.74
db	187
da	188
Y1	1.4
B_	57
Sb	14
C0	890
Sa	10
D_	260
Z_	27
C_	43
C0r	90500
DA_	21.743
Iso	4EC
DE_	235.768
D_b	249
DI_	193.731
SBRG	20
SDM_	214.75
D_a2	232
KBRG	3111
yobi	HR32034XJ

D_a1	248
mass	10.6
TC-RA	436
r min.	3 mm
Weight	10,6 Kg
TC-DA1	22.825
TC-DA2	20.661
TC-SLR	41.5
Da min	232 mm
LangID	1
ALPHA_	16.5
Db min.	249 mm
Oil rpm	1700
db max.	187 mm
Da max.	248 mm
ra max.	2,5 mm
hidYobi	HR32034XJ
da min.	188 mm
T-ALP21	33
rb max.	2 mm
T-ALP22	0
T-ALP23	0
GRS rpm	1200
inner r	3
outer r	2.5
r1 min.	2,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	3
inner ra	2.5
outer rb	2
TC-BET22	0

Size (mm)	170x260x57
Width (mm)	57
Prod_Type3	TRBSR_MD_A
Bearing number	HR32034XJ
Bore Diameter (mm)	170
Outer Diameter (mm)	260
Calculation factor (e)	0,44
Calculation factor (Y0)	0,74
(Oil) Lubrication Speed	1700 r/min
(Grease) Lubrication Speed	1200 r/min
Basic dynamic load rating (C)	505 kN
Basic static load rating (C0)	890 kN