



Bearing No. HR32056XJ

D	420 mm
d	280 mm
T	87 mm
B	87 mm
C	65 mm
a	91,6 mm
e	0.46
Cr	120000
Y0	0.72
db	305
da	307
Y1	1.3
B_	87
Sb	22
C0	2240
Sa	14
D_	420
Z_	28
C_	65
C0r	228000
DA_	34.218
Iso	4FC
DE_	381.684
D_b	402
DI_	316.178
SBRG	20
SDM_	348.931
D_a2	374
KBRG	3111
yobi	HR32056XJ

D_a1	402
mass	40.6
TC-RA	685.5
r min.	5 mm
Weight	40,6 Kg
TC-DA1	35.887
TC-DA2	32.549
TC-SLR	64
Da min	374 mm
LangID	1
ALPHA_	17
Db min.	402 mm
Oil rpm	1000
db max.	305 mm
Da max.	402 mm
ra max.	4 mm
hidYobi	HR32056XJ
da min.	307 mm
T-ALP21	34
rb max.	3 mm
T-ALP22	0
T-ALP23	0
GRS rpm	710
inner r	5
outer r	4
r1 min.	4 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	3
inner ra	4
outer rb	3
TC-BET22	0

Size (mm)	280x420x87
Width (mm)	87
Prod_Type3	TRBSR_MD_A
Bearing number	HR32056XJ
Bore Diameter (mm)	280
Outer Diameter (mm)	420
Calculation factor (e)	0,46
Calculation factor (Y0)	0,72
(Oil) Lubrication Speed	1000 r/min
(Grease) Lubrication Speed	710 r/min
Basic dynamic load rating (C)	1180 kN
Basic static load rating (C0)	2240 kN