




Bearing No. 6008-2Z/VA208

D	68 mm
d	40 mm
B	15 mm
C	15 mm
d1	49,2 mm
D2	61,1 mm
Noun	Bearing
Bore	1.575 Inch 40 Millimeter
Weight	0,19 Kg
UNSPSC	31171504
series:	60
r1 min.	1 mm
r2 min.	1 mm
Category	Single Row Ball Bearing
Snap Ring	No
Inventory	0.0
Size (mm)	40x68x15
Enclosure	2 Metal Shields
Width (mm)	15
bore type:	Round
Mass bearing	0.2 kg
Weight / LBS	0.454
maximum rpm:	80 RPM
Inch - Metric	Metric
Cage Material	Graphite
Temperature -	150 to +350 °
Product Group	B00308
closure type:	Double Shielded
bore diameter:	40 mm

Limiting speed	80 r/min
overall width:	15 mm
fillet radius:	1 mm
cage material:	Graphite
Bearing number	6008-2Z/VA208
Keyword String	Ball
Other Features	Deep Groove Extreme Temperature Variant
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	40MM Bore; 68MM Outside Diameter; 15MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; Segmented Cage Internal Special Features; C0-Medium Internal Cle
Manufacturer URL	http://www.skf.com
Outer Race Width	0.591 Inch 15 Millimeter
Outside Diameter	2.677 Inch 68 Millimeter
Inner Race Width	0 Inch 0 Millimeter
outer ring width:	15 mm
Weight / Kilogram	0.194
Manufacturer Name	SKF
outside diameter:	68 mm
precision rating:	Not Rated
Bore Diameter (mm)	40
Internal Clearance	C0-Medium
r _a max.	1 mm

D _a max.	63.4 mm
d _a max.	49.2 mm
d _a min.	44.6 mm
internal clearance:	C0
Outer Diameter (mm)	68
Minimum Buy Quantity	N/A
resistance features:	Corrosion Resistant, Extreme Temperature
r _{1,2} min.	1 mm
D ₂ ?	61.1 mm
static load capacity:	11 kN
d ₁ ?	49.25 mm
row type & fill slot:	Single Row Non-Fill Slot
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6008-2Z/VA208
Internal Special Features	Segmented Cage
Basic dynamic load rating C	17.8 kN
Limiting temperature T max.	350 °C
operating temperature range:	-240 to +660 °F
Basic static load rating (C0)	11 kN
Maximum Capacity / Filling Slot	No
Basic static load rating C ₀	11 kN