



Bearing No. 6008DDU

r	1
d	40 mm
D	68 mm
B	15 mm
C	15 mm
D_	68
C0	11.5
Z_	12
ra	1
fo	15.3
B_	15
DI_	46.562
SRI	4.11
DE_	62.438
SRE	4.11
DA_	7.938
D_a	63
KBRG	6161
SBRG	10
SRIN	-0.02
bomp	0
SREX	0.02
yobi	6008DDU
SRIX	0.02
mass	0.19
SDM_	54.5
SREN	-0.02
Bore	1.575 Inch 40 Millimeter
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	45
r min.	1 mm
Weight	0,19 Kg
ALPHA_	0
C_conv	16800
da max	47,5 mm
GRS rpm	6000
Da max.	63 mm
ra max.	1 mm
da min.	45 mm
hidYobi	6008DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	40x68x15
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	15
Prod_Type3	DGBB_SR_DD
Weight / LBS	0.419
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6008DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Inner Race Width	0 Inch 0 Millimeter

Outside Diameter	2.677 Inch 68 Millimeter
Long Description	40MM Bore; 68MM Outside Diameter; 15MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.591 Inch 15 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	0.188
Internal Clearance	C0-Medium
Bore Diameter (mm)	40
Outer Diameter (mm)	68
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6008DDU
Internal Special Features	No
(Grease) Lubrication Speed	6 000 r/min
Basic static load rating (C0)	11,5 kN
Basic dynamic load rating (C)	16,8 kN
Maximum Capacity / Filling Slot	No