



### Bearing No. HR30332J

D	340 mm
d	160 mm
T	75 mm
B	68 mm
C	58 mm
a	62,9 mm
e	0.35
Cr	89000
Y0	0.96
db	201
da	187
Y1	1.7
B_	68
Sb	17
C0	1110
Sa	10
D_	340
Z_	15
C_	58
C0r	113000
DA_	46.104
Iso	2GB
DE_	296.091
D_b	310
DI_	205.47
SBRG	3
SDM_	250.781
D_a2	293
KBRG	3111
yobi	HR30332J

D_a1	322
mass	29.2
TC-RA	684.861
r min.	5 mm
Weight	29,2 Kg
TC-DA1	47.799
TC-DA2	44.41
TC-SLR	49
Da min	293 mm
LangID	1
ALPHA_	12.953
Db min.	310 mm
Oil rpm	1400
db max.	201 mm
Da max.	322 mm
ra max.	4 mm
hidYobi	HR30332J
da min.	187 mm
T-ALP21	25
rb max.	3 mm
T-ALP22	54
T-ALP23	20
GRS rpm	1100
inner r	5
outer r	4
r1 min.	4 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	4
inner ra	4
outer rb	3
TC-BET22	0

Size (mm)	160x340x75
Width (mm)	75
Prod_Type3	TRBSR_MD_A
Bearing number	HR30332J
Bore Diameter (mm)	160
Outer Diameter (mm)	340
Calculation factor (e)	0,35
Calculation factor (Y0)	0,96
(Oil) Lubrication Speed	1400 r/min
(Grease) Lubrication Speed	1100 r/min
Basic dynamic load rating (C)	870 kN
Basic static load rating (C0)	1110 kN