




Bearing No. 6008NR

f	1,65 mm
d	40 mm
D	68 mm
B	15 mm
C	15 mm
a	2,49 mm
b	2,05 mm
Cr	20.9
f0	15.2
Cu	0.690
D2	74,6 mm
D1	64,82 mm
C0r	11.5
Bore	1.575 Inch 40 Millimeter
Noun	Bearing
r min.	1 mm
r(min)	1
UNSPSC	31171504
Weight	0,192 Kg
r1(min)	0.5
da(min)	45
D2(min)	74.6
Da(max)	63
rb(max)	0.5
ra(max)	1
Dx(min)	76
r0 max.	0,6 mm
r1 min.	0,5 mm
da min.	45 mm

Cy(max)	3.89
Da max.	63 mm
Category	Single Row Ball Bearing
Oil lub.	12000
Snap Ring	Yes
Size (mm)	40x68x15
Inventory	0.0
Enclosure	Open
Width (mm)	15
Grease lub.	10000
f{0.05)	1.65
Bearing No.	6008NR
Weight / LBS	0.42329
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
Bearing number	6008NR
Other Features	Deep Groove With Snap Ring
Keyword String	Ball
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Manufacturer URL	http://www.koyousa.com
Outside Diameter	2.677 Inch 68 Millimeter
(Refer.)Mass(kg)	0.192
Long Description	40MM Bore; 68MM Outside Diameter; 15MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage

Outer Race Width	0.591 Inch 15 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Weight / Kilogram	0
Manufacturer Name	KOYO
Internal Clearance	C0-Medium
Bore Diameter (mm)	40
Outer Diameter (mm)	68
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	12000 r/min
Internal Special Features	No
(Grease) Lubrication Speed	10000 r/min
Basic static load rating (C0)	11,5 kN
Basic dynamic load rating (C)	16,7 kN
Maximum Capacity / Filling Slot	No