




Bearing No. 6008VV

D	68 mm
d	40 mm
B	15 mm
C	15 mm
r	1
Z_	12
B_	15
D_	68
ra	1
C0	11.5
fo	15.3
DI_	46.562
SRI	4.11
D_a	63
DE_	62.438
DA_	7.938
SRE	4.11
SRIN	-0.02
SBRG	10
yobi	6008VV
SDM_	54.5
SREX	0.02
KBRG	6151
bomp	0
mass	0.19
Bore	1.575 Inch 40 Millimeter
SRIX	0.02
SREN	-0.02
Noun	Bearing

ALPHA_	0
da min	45
LangID	1
r min.	1 mm
UNSPSC	31171504
da max	47,5 mm
C_conv	16800
Weight	0,19 Kg
ra max.	1 mm
hidYobi	6008VV
GRS rpm	10000
da min.	45 mm
Da max.	63 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Size (mm)	40x68x15
Enclosure	2 Seals
Inventory	0.0
Width (mm)	15
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.184
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Bearing number	6008VV
Keyword String	Ball
Enclosure Type	Non-Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.591 Inch 15 Millimeter
Outside Diameter	2.677 Inch 68

	Millimeter
Long Description	40MM Bore; 68MM Outside Diameter; 15MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Weight / Kilogram	0.19
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	40
Outer Diameter (mm)	68
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6008VV
Internal Special Features	No
(Grease) Lubrication Speed	10 000 r/min
Basic static load rating (C0)	11,5 kN
Basic dynamic load rating (C)	16,8 kN
Maximum Capacity / Filling Slot	No