



Bearing No. 30244

D	400 mm
d	220 mm
T	72 mm
B	65 mm
C	54 mm
a	74,6 mm
e	0.4
Cr	82500
Y0	0.82
db	267
da	247
Y1	1.5
B_	65
Sb	18
C0	1150
Sa	11
D_	400
Z_	18
C_	54
C0r	117000
DA_	41.623
Iso	-
DE_	352.47
D_b	367
DI_	271.583
SBRG	2
SDM_	312.027
D_a2	350
KBRG	3111
yobi	30244

D_a1	382
mass	33.6
TC-RA	703.847
r min.	5 mm
Weight	33,6 Kg
TC-DA1	42.986
TC-DA2	40.259
TC-SLR	45
Da min	350 mm
LangID	1
ALPHA_	15
Db min.	367 mm
Oil rpm	1100
db max.	267 mm
Da max.	382 mm
ra max.	4 mm
hidYobi	30244
da min.	247 mm
T-ALP21	30
rb max.	3 mm
T-ALP22	0
T-ALP23	0
GRS rpm	850
inner r	5
outer r	4
r1 min.	4 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	3
inner ra	4
outer rb	3
TC-BET22	30

Size (mm)	220x400x72
Width (mm)	72
Prod_Type3	TRBSR_MD_A
Bearing number	30244
Bore Diameter (mm)	220
Outer Diameter (mm)	400
Calculation factor (e)	0,4
Calculation factor (Y0)	0,82
(Oil) Lubrication Speed	1100 r/min
(Grease) Lubrication Speed	850 r/min
Basic dynamic load rating (C)	810 kN
Basic static load rating (C0)	1150 kN