



Bearing No. 23028-E1-K-TVPB + H3028

| | |
|----------------|---|
| | H3028 / Adapter sleeve |
| e | 0,22 |
| D | 210 mm |
| B | 53 mm |
| l | 82 mm |
| c | 24 mm |
| m | 5,8 kg / Weight |
| d | 140 mm |
| Size (mm) | 125x210x53 |
| Width (mm) | 53 |
| m_1 | 3,3 kg |
| C_r | 570000 N / Dynamic load rating (radial) |
| n_s | 9,5 mm |
| d_s | 4,8 mm |
| n_B | 76000 N / Fatigue limit load, radial |
| d_2 | 155,4 mm |
| D_m | 165 mm |
| D_1 | 192,3 mm |
| Y_2 | 4,57 |
| Y_0 | 3 |
| n_G | 3450 1/min / Limiting speed |
| Y_1 | 3,07 |
| C_{Or} | 800000 N / Static load rating (radial) |
| Bearing number | 23028-E1-K-TVPB + H3028 |
| d_{1H} | 125 mm |

| | |
|---------------------|----------|
| r_{\min} | 2 mm |
| $r_{a \max}$ | 2 mm |
| $d_{a \max}$ | 155 mm |
| $D_{a \max}$ | 201,2 mm |
| $B_{a \min}$ | 8 mm |
| $d_{b \min}$ | 147 mm |
| Bore Diameter (mm) | 125 |
| Outer Diameter (mm) | 210 |