




Bearing No. HR30232J

D	290 mm
d	160 mm
T	52 mm
B	48 mm
C	40 mm
a	55 mm
e	0.44
Cr	54000
Y0	0.76
db	189
da	181
Y1	1.4
B_	48
Sb	12
C0	730
Sa	8
D_	290
Z_	20
C_	40
C0r	74500
DA_	32.01
Iso	4GB
DE_	256.558
D_b	269
DI_	193.261
SBRG	2
SDM_	224.91
D_a2	253
KBRG	3111
yobi	HR30232J

D_a1	276
mass	13.7
TC-RA	475.487
r min.	4 mm
Weight	13,7 Kg
TC-DA1	33.186
TC-DA2	30.834
TC-SLR	34
Da min	253 mm
LangID	1
ALPHA_	16.173
Db min.	269 mm
Oil rpm	1600
db max.	189 mm
Da max.	276 mm
ra max.	3 mm
hidYobi	HR30232J
da min.	181 mm
T-ALP21	32
rb max.	2,5 mm
T-ALP22	20
T-ALP23	40
GRS rpm	1200
inner r	4
outer r	3
r1 min.	3 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	4
inner ra	3
outer rb	2.5
TC-BET22	0

Size (mm)	160x290x52
Width (mm)	52
Prod_Type3	TRBSR_MD_A
Bearing number	HR30232J
Bore Diameter (mm)	160
Outer Diameter (mm)	290
Calculation factor (e)	0,44
Calculation factor (Y0)	0,76
(Oil) Lubrication Speed	1600 r/min
(Grease) Lubrication Speed	1200 r/min
Basic dynamic load rating (C)	530 kN
Basic static load rating (C0)	730 kN