



Bearing No. 30264

C	75 mm
e	0.42
d	320 mm
D	580 mm
T	104 mm
B	92 mm
a	111,9 mm
Y0	0.79
Y1	1.44
Cu	273
Cr	2190
C0r	2770
a(mm)	111.9
r min.	6 mm
da max	370 mm
Da min	505 mm
r(min)	6
Weight	108 Kg
r1(min)	5
db(max)	370
da(min)	348
Sb(min)	28
Da(max)	558
Sa(min)	14
Da(min)	505
ra(max)	5
rb(max)	4
Db(min)	540
rb max.	4 mm
ra max.	5 mm

Db min.	540 mm
Da max.	558 mm
da min.	348 mm
r2 min.	5 mm
Oil lub.	660
Size (mm)	320x580x104
Width (mm)	104
Bearing No.	30264
Grease lub.	490
Bearing number	30264
(Refer.)Mass(kg)	108
Bore Diameter (mm)	320
Outer Diameter (mm)	580
Calculation factor (e)	0,42
Calculation factor (Y0)	0,79
(Oil) Lubrication Speed	660 r/min
(Grease) Lubrication Speed	490 r/min
Basic static load rating (C0)	2770 kN
Basic dynamic load rating (C)	1740 kN