



Bearing No. 30302JR

C	11 mm
e	0.29
d	15 mm
D	42 mm
T	14,25 mm
B	13 mm
a	10 mm
Y0	1.16
Y1	2.11
Cu	2.65
Cr	27.4
C0r	19.2
a(mm)	10.0
r min.	1 mm
da max	22 mm
Da min	35 mm
r(min)	1
Weight	0,098 Kg
r1(min)	1
db(max)	22
da(min)	20.5
Sb(min)	3
Da(max)	36.5
Sa(min)	2
Da(min)	35
ra(max)	1
rb(max)	1
Db(min)	38
rb max.	1 mm
ra max.	1 mm

Db min.	38 mm
Da max.	36,5 mm
da min.	20,5 mm
r2 min.	1 mm
Oil lub.	14000
Size (mm)	15x42x14.25
Width (mm)	14,25
Bearing No.	30302JR
Grease lub.	10000
Bearing number	30302JR
(Refer.)Mass(kg)	0.098
Bore Diameter (mm)	15
Outer Diameter (mm)	42
Calculation factor (e)	0,29
Calculation factor (Y0)	1,16
(Oil) Lubrication Speed	14000 r/min
(Grease) Lubrication Speed	10000 r/min
Basic static load rating (C0)	19,2 kN
Basic dynamic load rating (C)	21,9 kN