

Page 1/3

D_a1	43
mass	0.168
TC-RA	48.248
r min.	1,5 mm
Weight	0,168 Kg
TC-DA1	7.569
TC-DA2	5.942
TC-SLR	10.5
Da min	37 mm
LangID	1
ALPHA_	28.5
Db min.	49 mm
Oil rpm	10000
db max.	26 mm
Da max.	43 mm
ra max.	1,5 mm
hidYobi	30304D
da min.	34 mm
T-ALP21	57
rb max.	1,5 mm
T-ALP22	0
T-ALP23	0
GRS rpm	7100
inner r	1.5
outer r	1.5
r1 min.	1,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	9
inner ra	1.5
outer rb	1.5
TC-BET22	0

Size (mm)	20x52x16.25
Width (mm)	16,25
Prod_Type3	TRBSR_MD_A
Bearing number	30304D
Bore Diameter (mm)	20
Outer Diameter (mm)	52
Calculation factor (e)	0,81
Calculation factor (Y0)	0,41
(Oil) Lubrication Speed	10000 r/min
(Grease) Lubrication Speed	7100 r/min
Basic dynamic load rating (C)	25,3 kN
Basic static load rating (C0)	24,5 kN