




Bearing No. 6010

D	80 mm
d	50 mm
B	16 mm
C	16 mm
f0	15.5
Bore	1.969 Inch 50 Millimeter
Noun	Bearing
Mass	0.26 kg
Da max	75 mm
UNSPSC	31171504
r min.	1 mm
rs min	1 mm
da max	57,5 mm
da min	55 mm
Weight	0,261 Kg
ra max	1 mm
Da max.	75 mm
ra max.	1 mm
da min.	55 mm
series:	60
Category	Single Row Ball Bearing
Snap Ring	No
Inventory	0.0
Enclosure	Open
Size (mm)	50x80x16
Nlim (oil)	9,800 rpm
bore type:	Round
Width (mm)	16
Weight / LBS	0.575

maximum rpm:	9800 RPM
Nlim (grease)	8,400 rpm
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
closure type:	Open
Keyword String	Ball
bore diameter:	50 mm
cage material:	Steel
fillet radius:	1 mm
overall width:	16 mm
Bearing number	6010
Dynamic load, C	21.8 kN
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Static load, C0	16.6 kN
Manufacturer URL	http://www.ntnamerica.com
Outer Race Width	0.63 Inch 16 Millimeter
Outside Diameter	3.15 Inch 80 Millimeter
Long Description	50MM Bore; 80MM Outside Diameter; 16MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
outer ring width:	16 mm
inner ring width:	16 mm
bearing material:	High Carbon Chrome Steel
outside diameter:	80 mm
Weight / Kilogram	0.26

precision rating:	Class 0
Manufacturer Name	NTN
maximum rpm (oil):	9800 rpm
Internal Clearance	C3-Loose
Bore Diameter (mm)	50
Outer Diameter (mm)	80
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
maximum rpm (grease):	8400 rpm
static load capacity:	16600 N
row type & fill slot:	Single Row Non-Fill Slot
Radial clearance class	CN
dynamic load capacity:	21800 N
Fatigue limit load, Cu	0.75 kN
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	9 800 r/min
Manufacturer Item Number	6010
Internal Special Features	No
(Grease) Lubrication Speed	8 400 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	16,6 kN
Basic dynamic load rating (C)	21,8 kN
Max operating temperature, Tmax	120 °C
Min operating temperature, Tmin	-20 °C

Maximum Capacity / Filling Slot	No
Characteristic cage frequency, FTF	0.43 Hz
Characteristic inner ring frequency, BPFI	7.94 Hz
Characteristic outer ring frequency, BPF0	6.06 Hz
Characteristic rolling element frequency, BSF	7.31 Hz