



Bearing No. 7000C

a	-1.9 mm
d	10 mm
D	26 mm
B	8 mm
C	8 mm
r1	0.2 mm
a -	1,9 mm
Width	8 mm
Weight	0,022 Kg
r min.	0,3 mm
ra max.	0.3 mm
Da max.	24 mm
da min.	12 mm
r1 min.	0,15 mm
ra (max)	0.3 mm
Da1 (max)	24 mm
Da2 (max)	25 mm
da2 (min)	12 mm
da1 (min)	12 mm
Size (mm)	10x26x8
Enclosure	Open
Bore Type	Cylindrical Bore
Bore Size	10 mm
ra1 (max)	0.2 mm
Width (mm)	8
Configuration	Single Row
Bearing number	7000C
Angle (?)	15 °
Outside Diameter	26 mm
Static Load Rating	2,500 N

Bore Diameter (mm)	10
Dynamic Load Rating	5,350 N
Outer Diameter (mm)	26
Limiting Speed - Oil	61,000 rpm
Fillet Radius/Chamfer	0.3 mm
Limiting Speed - Grease	44,000 rpm
(Grease) Lubrication Speed	65000 r/min
Basic static load rating (C0)	2,5 kN
Basic dynamic load rating (C)	5,35 kN