



Bearing No. 7000CDT

C	8 mm
d	10 mm
B	8 mm
D	26 mm
r1	0.2 mm
2B	16 mm
a -	1.9 mm
Width	8 mm
r min.	0.3 mm
Weight	0.022 Kg
ra max.	0.15 mm
r1 min.	0.15 mm
da min.	12 mm
Da max.	25 mm
ra (max)	0.3 mm
da1 (min)	12 mm
Bore Size	10 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.2 mm
Size (mm)	10x26x8
da2 (min)	12 mm
Da2 (max)	25 mm
Da1 (max)	24 mm
Width (mm)	8
Configuration	Duplex
Bearing number	7000CDT
Angle (?)	15 °
Outside Diameter	26 mm
Static Load Rating	5,000 N

Bore Diameter (mm)	10
Dynamic Load Rating	8,700 N
Outer Diameter (mm)	26
Limiting Speed - Oil	49,000 rpm
Fillet Radius/Chamfer	0.3 mm
Limiting Speed - Grease	35,000 rpm
(Grease) Lubrication Speed	35000 r/min
Basic dynamic load rating (C)	8,7 kN
Basic static load rating (C0)	5 kN