



Bearing No. 7001 ACD/P4AH

K	0.5 mm
a	8.7 mm
d	12 mm
D	28 mm
B	8 mm
Ball - z	10
Size (mm)	28x12x8
Width (mm)	8
Mass bearing	0.021 kg
d_n	18 mm
D_1	22.9 mm
d_1	17.1 mm
C_1	4.9 mm
D_1	22.9 mm
d_2	17.1 mm
C_1	4.9 mm
d_1	17.1 mm
d_n	18 mm
d_2	17.1 mm
Bearing number	7001 ACD/P4AH
Preload class B	44 N/micron
Preload class A	34 N/micron
Preload class D	76 N/micron
G_{ref}	0.27 cm ³
Preload class C	57 N/micron
Number of balls z	10
Bore Diameter (mm)	28
r_b max.	0.2 mm
r_a max.	0.3 mm

D _b max.	26.6 mm
D _a max.	26 mm
d _a min.	14 mm
d _b min.	14 mm
Outer Diameter (mm)	12
r _a - max.	0.3 mm
D _a - max.	26 mm
d _b - min.	14 mm
d _a - min.	14 mm
r _{1,2} min.	0.3 mm
r _{3,4} min.	0.2 mm
Ball - D _w	4.762 mm
r _b - max.	0.2 mm
D _b - max.	26.6 mm
Calculation factor f	1.03
Calculation factor e	0.68
Calculation factor - f	1.03
r _{1,2} - min.	0.3 mm
r _{3,4} - min.	0.2 mm
Calculation factor - e	0.68
Ball diameter D _w	4.762 mm
Basic dynamic load rating C	4.36 kN
Preload class A G _A	25 N
Preload class B G _B	50 N
Preload class C G _C	100 N
Basic dynamic load rating - C	4.4 kN
Preload class D G _D	200 N
Preload class B - G _B	50 N
Preload class A - G _A	25 N
Preload class D - G _D	200 N

Preload class C - G_C	100 N
Fatigue load limit P_u	0.078 kN
Calculation factor f_1	0.99
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.02
Calculation factor f_{2C}	1.05
Calculation factor f_{2D}	1.08
Calculation factor f_{HC}	1
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Calculation factor - Y_0	0.76
Calculation factor - X_2	0.67
Calculation factor - f_1	0.99
Limiting speed for oil lubrication	90000 mm/min
Fatigue load limit - P_u	0.078 kN
Calculation factor - f_{2D}	1.08
Calculation factor - f_{HC}	1
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2B}	1.02
Calculation factor - f_{2A}	1
Limiting speed for grease lubrication	60000 r/min
Basic static load rating C_0	1.83 kN
Static axial stiffness, preload class A	34 N/ μ m
Static axial stiffness, preload class D	76 N/ μ m
Static axial stiffness, preload class C	57 N/ μ m
Static axial stiffness,	44 N/ μ m

preload class B	
Attainable speed for grease lubrication	60000 r/min
Basic static load rating - C_0	1.8 kN
Attainable speed for oil-air lubrication	90000 r/min
Reference grease quantity G_{ref}	0.27 cm ³
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67