



Bearing No. HM903247/HM903210

| | |
|---------------------------------|--------------------|
| R | 1,3 mm |
| a | 0,5 mm |
| d | 44,45 mm |
| D | 95,25 mm |
| T | 30,958 mm |
| B | 28,3 mm |
| C | 22,225 mm |
| r | 0,8 mm |
| Ab | 2,3 mm |
| Aa | 3,9 mm |
| Db | 81 mm |
| da | 54 mm |
| db | 61 mm |
| Da | 91 mm |
| Weight | 1,01 Kg |
| Size (mm) | 44.45x95.25x30.958 |
| Width (mm) | 30,958 |
| Factor (K) | 0,79 |
| Factor (G1) | 33,7 |
| Factor (Cg) | 0,0269 |
| Factor (G2) | 12,4 |
| Bearing number | HM903247/HM903210 |
| Bore Diameter (mm) | 44,45 |
| Outer Diameter (mm) | 95,25 |
| Calculation factor (e) | 0,74 |
| Basic static load rating (C0) | 132 kN |
| Basic dynamic load rating (C1) | 107 kN |
| Basic dynamic load rating (C90) | 27,6 |

| | |
|----------------------------------|----|
| Basic dynamic load rating (Ca90) | 35 |
|----------------------------------|----|