



Bearing No. NUP2208EG

C	23 mm
B	23 mm
D	80 mm
d	40 mm
Fw	49,5 mm
r1	1.1 mm
Width	23 mm
r min.	1,1 mm
Weight	0,743 Kg
r1 min.	1,1 mm
dd (min)	56 mm
Da (max)	73 mm
dc (min)	52 mm
db (max)	49 mm
db (min)	47 mm
ra (max)	1 mm
Bore Size	40 mm
ra1 (max)	1 mm
Bore Type	Cylindrical Bore
Size (mm)	40x80x23
Enclosure	Open
Width (mm)	23
Configuration	Single Row
Bearing number	NUP2208EG
Outside Diameter	80 mm
Radial Clearance	0.025 to 0.050 mm
Static Load Rating	77,500 N
Bore Diameter (mm)	40
Dynamic Load Rating	72,500 N
Outer Diameter (mm)	80

Limiting Speed - Oil	9,000 rpm
Fillet Radius/Chamfer	1.1 mm
Limiting Speed - Grease	7,500 rpm
(Grease) Lubrication Speed	7500 r/min
Inside Ring Outside Diameter	49.5 mm
Basic static load rating (C0)	77,5 kN
Basic dynamic load rating (C)	72,5 kN