



Bearing No. 7001 ACE/HCP4AH

K	0.5 mm
a	8.8 mm
d	12 mm
D	28 mm
B	8 mm
Ball - z	12
Size (mm)	28x12x8
Width (mm)	8
Mass bearing	0.019 kg
$d_n$	18.5 mm
$D_1$	22.45 mm
$d_1$	17.5 mm
$C_1$	4.9 mm
$D_1$	22.45 mm
$d_2$	16.5 mm
$C_1$	4.9 mm
$d_1$	17.5 mm
$d_n$	18.5 mm
$d_2$	16.5 mm
Bearing number	7001 ACE/HCP4AH
Preload class A	37 N/micron
Preload class B	56 N/micron
Preload class C	73 N/micron
$G_{ref}$	0.31 cm <sup>3</sup>
Number of balls z	12
Bore Diameter (mm)	28
$r_b$ max.	0.15 mm
$r_a$ max.	0.3 mm
$D_b$ max.	26.6 mm

$D_a$ max.	26 mm
$d_a$ min.	14 mm
$d_b$ min.	14 mm
Outer Diameter (mm)	12
$r_a$ - max.	0.3 mm
$r_{3,4}$ min.	0.15 mm
$D_a$ - max.	26 mm
$d_b$ - min.	14 mm
$r_{1,2}$ min.	0.3 mm
Ball - $D_w$	3.969 mm
$r_b$ - max.	0.15 mm
$D_b$ - max.	26.6 mm
Calculation factor f	1.02
Calculation factor e	0.68
$d_a$ - min.	14 mm
Calculation factor - f	1.02
$r_{3,4}$ - min.	0.15 mm
$r_{1,2}$ - min.	0.3 mm
Calculation factor - e	0.68
Ball diameter $D_w$	3.969 mm
Basic dynamic load rating C	3.07 kN
Preload class A $G_A$	28 N
Preload class B $G_B$	85 N
Preload class C $G_C$	170 N
Basic dynamic load rating - C	3.1 kN
Preload class B - $G_B$	85 N
Preload class C - $G_C$	170 N
Preload class A - $G_A$	28 N
Fatigue load limit $P_u$	0.054 kN
Calculation factor $f_1$	0.99

Calculation factor $f_{2C}$	1.06
Calculation factor $f_{2B}$	1.03
Calculation factor $f_{HC}$	1.01
Calculation factor $f_{2A}$	1
Calculation factor - $f_1$	0.99
Limiting speed for oil lubrication	133000 mm/min
Fatigue load limit - $P_u$	0.054 kN
Calculation factor - $Y_0$	0.76
Calculation factor - $Y_1$	0.92
Calculation factor - $X_2$	0.67
Calculation factor - $Y_2$	1.41
Calculation factor - $f_{HC}$	1.01
Calculation factor - $f_{2C}$	1.06
Calculation factor - $f_{2B}$	1.03
Calculation factor - $f_{2A}$	1
Limiting speed for grease lubrication	88000 r/min
Basic static load rating $C_0$	1.27 kN
Static axial stiffness, preload class C	73 N/ $\mu$ m
Attainable speed for grease lubrication	88000 r/min
Static axial stiffness, preload class B	56 N/ $\mu$ m
Static axial stiffness, preload class A	37 N/ $\mu$ m
Attainable speed for oil-air lubrication	133000 r/min
Basic static load rating - $C_0$	1.3 kN
Reference grease	0.31 cm <sup>3</sup>

quantity $G_{ref}$	
Calculation factor (single, tandem) $Y_2$	0.87
Calculation factor (single, tandem) $Y_0$	0.38
Calculation factor (single, tandem) $X_2$	0.41
Calculation factor (back- to-back, face-to-face) $Y_1$	0.92
Calculation factor (back- to-back, face-to-face) $Y_2$	1.41
Calculation factor (back- to-back, face-to-face) $Y_0$	0.76
Calculation factor (back- to-back, face-to-face) $X_2$	0.67