



Bearing No. 23228-E1-TVPB

|                    |                                          |
|--------------------|------------------------------------------|
| m                  | 17,1 kg / Weight                         |
| d                  | 140 mm                                   |
| D                  | 250 mm                                   |
| B                  | 88 mm                                    |
| e                  | 0,33                                     |
| Size (mm)          | 140x250x88                               |
| Width (mm)         | 88                                       |
| $n_s$              | 12,2 mm                                  |
| $d_s$              | 6,3 mm                                   |
| $Y_1$              | 2,04                                     |
| $Y_2$              | 3,04                                     |
| $Y_0$              | 2                                        |
| $d_2$              | 162 mm                                   |
| $D_1$              | 216 mm                                   |
| $n_G$              | 2600 1/min / Limiting speed              |
| $n_B$              | 1580 1/min                               |
| $C_r$              | 1090000 N / Dynamic load rating (radial) |
| $C_{Or}$           | 1400000 N / Static load rating (radial)  |
| Bearing number     | 23228-E1-TVPB                            |
| $C_{ur}$           | 112000 N / Fatigue limit load, radial    |
| $r_{min}$          | 3 mm                                     |
| $r_{a \max}$       | 2,5 mm                                   |
| $d_{a \min}$       | 154 mm                                   |
| $D_{a \max}$       | 236 mm                                   |
| Bore Diameter (mm) | 140                                      |
|                    |                                          |



|                     |     |
|---------------------|-----|
| Outer Diameter (mm) | 250 |
|---------------------|-----|