




Bearing No. 7001DT

D	28 mm
a	1.7 mm
C	8 mm
B	8 mm
d	12 mm
r1	0.2 mm
2B	16 mm
Width	8 mm
r min.	0.3 mm
Weight	0.024 Kg
ra max.	0.15 mm
r1 min.	0.15 mm
da min.	14 mm
Da max.	27 mm
ra (max)	0.3 mm
da1 (min)	14 mm
Bore Size	12 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.2 mm
Size (mm)	12x28x8
da2 (min)	14 mm
Da2 (max)	27 mm
Da1 (max)	26 mm
Width (mm)	8
Configuration	Duplex
Bearing number	7001DT
Angle (?)	30 °
Outside Diameter	28 mm
Static Load Rating	5,700 N

Bore Diameter (mm)	12
Dynamic Load Rating	8,800 N
Outer Diameter (mm)	28
Limiting Speed - Oil	23,000 rpm
Fillet Radius/Chamfer	0.3 mm
Limiting Speed - Grease	18,000 rpm
(Grease) Lubrication Speed	18000 r/min
Basic dynamic load rating (C)	8,8 kN
Basic static load rating (C0)	5,7 kN