




Bearing No. 6011-2Z/VA208

D	90 mm
d	55 mm
B	18 mm
Bore	2.165 Inch 55 Millimeter
Noun	Bearing
UNSPSC	31171504
Category	Single Row Ball Bearing
Inventory	0.0
Enclosure	2 Metal Shields
Size (mm)	90x55x18
Snap Ring	No
Width (mm)	18
Mass bearing	0.4 kg
Weight / LBS	0.4
Inch - Metric	Metric
Cage Material	Graphite
Product Group	B00308
D ₂	81.5 mm
d ₁	66.3 mm
Other Features	Deep Groove Extreme Temperature Variant
Keyword String	Ball
Bearing number	6011-2Z/VA208
Limiting speed	60 r/min
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.skf.com
Outside Diameter	3.543 Inch 90 Millimeter
Outer Race Width	0.709 Inch 18

	Millimeter
Long Description	55MM Bore; 90MM Outside Diameter; 18MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; Segmented Cage Internal Special Features; C0-Medium Internal Cle
Inner Race Width	0 Inch 0 Millimeter
Weight / Kilogram	0
Manufacturer Name	SKF
d _a min.	61 mm
Internal Clearance	C0-Medium
d _a max.	66.2 mm
D _a max.	84 mm
Bore Diameter (mm)	90
r _a max.	1 mm
Outer Diameter (mm)	55
r _{1,2} min.	1.1 mm
Minimum Buy Quantity	N/A
d _a - min.	61 mm
d _a - max.	66.2 mm
D _a - max.	84 mm
r _a - max.	1 mm
d ₁ ?	66.3 mm
D ₂ ?	81.5 mm
Harmonized Tariff Code	8482.10.50.68
r _{1,2} - min.	1.1 mm
Limiting temperature - T	350 °C
Internal Special Features	Segmented Cage
Basic dynamic load	29.6 kN

rating C	
Limiting temperature T max.	350 °C
Basic dynamic load rating - C	29.6 kN
Maximum Capacity / Filling Slot	No
Basic static load rating C ₀	21.2 kN
Basic static load rating - C ₀	21.2 kN