



Bearing No. 7002CDT

C	9 mm
d	15 mm
B	9 mm
D	32 mm
r1	0.2 mm
2B	18 mm
a -	1.8 mm
Width	9 mm
r min.	0.3 mm
Weight	0.035 Kg
ra max.	0.15 mm
r1 min.	0.15 mm
da min.	17 mm
Da max.	31 mm
ra (max)	0.3 mm
da1 (min)	17 mm
Bore Size	15 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.2 mm
Size (mm)	15x32x9
da2 (min)	17 mm
Da2 (max)	31 mm
Da1 (max)	30 mm
Width (mm)	9
Configuration	Duplex
Bearing number	7002CDT
Angle (?)	15 °
Outside Diameter	32 mm
Static Load Rating	7,450 N

Bore Diameter (mm)	15
Dynamic Load Rating	10,800 N
Outer Diameter (mm)	32
Limiting Speed - Oil	38,000 rpm
Fillet Radius/Chamfer	0.3 mm
Limiting Speed - Grease	27,000 rpm
(Grease) Lubrication Speed	27000 r/min
Basic dynamic load rating (C)	10,8 kN
Basic static load rating (C0)	7,45 kN