



Bearing No. NUP210R

|            |          |
|------------|----------|
| C          | 20 mm    |
| d          | 50 mm    |
| D          | 90 mm    |
| B          | 20 mm    |
| B2         | -        |
| Cu         | 9.85     |
| Ew         | -        |
| d1         | -        |
| B1         | -        |
| Cr         | 82.5     |
| Fw         | 59.5 mm  |
| C0r        | 71.9     |
| r min.     | 1.1 mm   |
| Weight     | 0.497 Kg |
| r(min)     | 1.1      |
| da(min)    | 56.5     |
| db(min)    | 56.5     |
| db(max)    | 58       |
| dc(min)    | -        |
| r1(min)    | 1.1      |
| dd(min)    | -        |
| Da(max)    | 83.5     |
| Db(max)    | -        |
| Db(min)    | -        |
| r1 min.    | 1.1 mm   |
| ra(max)    | 1        |
| rb(max)    | 1        |
| Oil lub.   | 8500     |
| Size (mm)  | 50x90x20 |
| Width (mm) | 20       |
|            |          |

|                               |            |
|-------------------------------|------------|
| Grease lub.                   | 7100       |
| Bearing No.                   | NUP210R    |
| Bearing number                | NUP210R    |
| (Refer.)Mass(kg)              | 0.525      |
| Bore Diameter (mm)            | 50         |
| Outer Diameter (mm)           | 90         |
| (Grease) Lubrication Speed    | 7100 r/min |
| Basic static load rating (C0) | 71.9 kN    |
| Basic dynamic load rating (C) | 66.1 kN    |