



Bearing No. 7005 ACD/HCP4A

D	47 mm
d	25 mm
B	12 mm
a	14.5 mm
Ball - z	14
Size (mm)	47x25x12
Width (mm)	12
Mass bearing	0.07 kg
d_n	33.4 mm
d_n	33.4 mm
D_1	39.9 mm
d_1	32.1 mm
d_2	32.1 mm
D_1	39.9 mm
d_2	32.1 mm
d_1	32.1 mm
Bearing number	7005 ACD/HCP4A
Preload class B	92 N/micron
Preload class A	71 N/micron
Preload class D	159 N/micron
Preload class C	119 N/micron
G_{ref}	1.02 cm ³
Number of balls z	14
Bore Diameter (mm)	47
r_b max.	0.3 mm
r_a max.	0.6 mm
D_b max.	45 mm
D_a max.	43.8 mm
d_a min.	28.2 mm

d _b min.	28.2 mm
Outer Diameter (mm)	25
D _b - max.	45 mm
d _b - min.	28.2 mm
Ball - D _w	6.35 mm
r _{1,2} min.	0.6 mm
r _{3,4} min.	0.3 mm
d _a - min.	28.2 mm
r _a - max.	0.6 mm
D _a - max.	43.8 mm
r _b - max.	0.3 mm
Calculation factor f	1.05
Calculation factor e	0.68
r _{1,2} - min.	0.6 mm
r _{3,4} - min.	0.3 mm
Calculation factor - e	0.68
Calculation factor - f	1.05
Ball diameter D _w	6.35 mm
Basic dynamic load rating C	9.23 kN
Preload class C G _C	240 N
Preload class B G _B	120 N
Preload class A G _A	60 N
Preload class D G _D	480 N
Basic dynamic load rating - C	9.2 kN
Preload class B - G _B	120 N
Preload class D - G _D	480 N
Preload class C - G _C	240 N
Preload class A - G _A	60 N
Fatigue load limit P _u	0.212 kN
Calculation factor f ₁	0.99

Calculation factor f_{2A}	1
Calculation factor f_{2C}	1.05
Calculation factor f_{2B}	1.02
Calculation factor f_{2D}	1.08
Calculation factor f_{HC}	1.02
Calculation factor - X_2	0.67
Calculation factor - f_1	0.99
Calculation factor - Y_1	0.92
Limiting speed for oil lubrication	60000 mm/min
Calculation factor - Y_0	0.76
Fatigue load limit - P_u	0.212 kN
Calculation factor - Y_2	1.41
Calculation factor - f_{HC}	1.02
Calculation factor - f_{2A}	1
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2B}	1.02
Calculation factor - f_{2D}	1.08
Limiting speed for grease lubrication	40000 r/min
Basic static load rating C_0	5 kN
Static axial stiffness, preload class B	92 N/ μm
Attainable speed for grease lubrication	40000 r/min
Static axial stiffness, preload class D	159 N/ μm
Static axial stiffness, preload class C	119 N/ μm
Static axial stiffness, preload class A	71 N/ μm
Basic static load rating -	5 kN

C ₀	
Attainable speed for oil-air lubrication	60000 r/min
Reference grease quantity G _{ref}	1.02 cm ³
Calculation factor (single, tandem) Y ₂	0.87
Calculation factor (single, tandem) Y ₀	0.38
Calculation factor (single, tandem) X ₂	0.41
Calculation factor (back-to-back, face-to-face) Y ₁	0.92
Calculation factor (back-to-back, face-to-face) Y ₂	1.41
Calculation factor (back-to-back, face-to-face) Y ₀	0.76
Calculation factor (back-to-back, face-to-face) X ₂	0.67