


Bearing No. 7005 ACE/P4A

| | |
|--------------------|---------------------|
| D | 47 mm |
| d | 25 mm |
| B | 12 mm |
| a | 14.4 mm |
| Ball - z | 14 |
| Size (mm) | 47x25x12 |
| Width (mm) | 12 |
| Mass bearing | 0.074 kg |
| d_n | 33.1 mm |
| d_n | 33.1 mm |
| D_1 | 39.21 mm |
| d_1 | 31.6 mm |
| d_2 | 29.8 mm |
| D_1 | 39.21 mm |
| d_2 | 29.8 mm |
| d_1 | 31.6 mm |
| Bearing number | 7005 ACE/P4A |
| Preload class A | 59 N/micron |
| G_{ref} | 1.3 cm ³ |
| Preload class C | 117 N/micron |
| Preload class B | 89 N/micron |
| Number of balls z | 14 |
| Bore Diameter (mm) | 47 |
| r_b max. | 0.3 mm |
| r_a max. | 0.6 mm |
| D_b max. | 44.6 mm |
| D_a max. | 43.8 mm |
| d_a min. | 28.2 mm |
| d_b min. | 28.2 mm |

| | |
|------------------------------------|----------|
| Outer Diameter (mm) | 25 |
| D _b - max. | 44.6 mm |
| d _a - min. | 28.2 mm |
| Calculation factor e | 0.68 |
| Calculation factor f | 1.05 |
| r _b - max. | 0.3 mm |
| D _a - max. | 43.8 mm |
| r _a - max. | 0.6 mm |
| r _{3,4} min. | 0.3 mm |
| r _{1,2} min. | 0.6 mm |
| Ball - D _w | 6.35 mm |
| d _b - min. | 28.2 mm |
| r _{1,2} - min. | 0.6 mm |
| r _{3,4} - min. | 0.3 mm |
| Calculation factor - e | 0.68 |
| Calculation factor - f | 1.05 |
| Basic dynamic load rating C | 7.93 kN |
| Ball diameter D _w | 6.35 mm |
| Preload class B G _B | 210 N |
| Preload class C G _C | 430 N |
| Basic dynamic load rating - C | 7.9 kN |
| Preload class A G _A | 70 N |
| Preload class B - G _B | 210 N |
| Preload class C - G _C | 430 N |
| Preload class A - G _A | 70 N |
| Fatigue load limit P _u | 0.166 kN |
| Calculation factor f ₁ | 0.99 |
| Calculation factor f _{2C} | 1.06 |
| Calculation factor f _{2A} | 1 |
| Calculation factor f _{HC} | 1 |

| | |
|---|---------------------|
| Calculation factor f_{2B} | 1.03 |
| Limiting speed for oil lubrication | 63000 mm/min |
| Fatigue load limit - P_u | 0.166 kN |
| Calculation factor - f_1 | 0.99 |
| Calculation factor - Y_2 | 1.41 |
| Calculation factor - X_2 | 0.67 |
| Calculation factor - Y_1 | 0.92 |
| Calculation factor - Y_0 | 0.76 |
| Calculation factor - f_{HC} | 1 |
| Calculation factor - f_{2A} | 1 |
| Calculation factor - f_{2C} | 1.06 |
| Calculation factor - f_{2B} | 1.03 |
| Limiting speed for grease lubrication | 42000 r/min |
| Basic static load rating C_0 | 3.9 kN |
| Static axial stiffness, preload class B | 89 N/ μ m |
| Static axial stiffness, preload class A | 59 N/ μ m |
| Attainable speed for grease lubrication | 42000 r/min |
| Static axial stiffness, preload class C | 117 N/ μ m |
| Basic static load rating - C_0 | 3.9 kN |
| Attainable speed for oil-air lubrication | 63000 r/min |
| Reference grease quantity G_{ref} | 1.3 cm ³ |
| Calculation factor (single, tandem) Y_2 | 0.87 |
| Calculation factor | 0.38 |

| | |
|---|------|
| (single, tandem) Y_0 | |
| Calculation factor (single, tandem) X_2 | 0.41 |
| Calculation factor (back-to-back, face-to-face) Y_1 | 0.92 |
| Calculation factor (back-to-back, face-to-face) Y_2 | 1.41 |
| Calculation factor (back-to-back, face-to-face) Y_0 | 0.76 |
| Calculation factor (back-to-back, face-to-face) X_2 | 0.67 |