



Bearing No. 7005 ACE/P4AH1

K	0.5 mm
a	14.4 mm
d	25 mm
D	47 mm
B	12 mm
Ball - z	14
Size (mm)	47x25x12
Width (mm)	12
Mass bearing	0.074 kg
d <sub>n</sub>	33.1 mm
D <sub>1</sub>	39.21 mm
d <sub>1</sub>	31.6 mm
C <sub>1</sub>	3.72 mm
D <sub>1</sub>	39.21 mm
d <sub>2</sub>	29.8 mm
C <sub>1</sub>	3.72 mm
d <sub>1</sub>	31.6 mm
d <sub>n</sub>	33.1 mm
d <sub>2</sub>	29.8 mm
Bearing number	7005 ACE/P4AH1
Preload class A	59 N/micron
Preload class B	89 N/micron
Preload class C	117 N/micron
G <sub>ref</sub>	1.3 cm <sup>3</sup>
Number of balls z	14
Bore Diameter (mm)	47
r <sub>b</sub> max.	0.3 mm
r <sub>a</sub> max.	0.6 mm
D <sub>b</sub> max.	44.6 mm

D <sub>a</sub> max.	43.8 mm
d <sub>a</sub> min.	28.2 mm
d <sub>b</sub> min.	28.2 mm
Outer Diameter (mm)	25
r <sub>a</sub> - max.	0.6 mm
r <sub>3,4</sub> min.	0.3 mm
D <sub>a</sub> - max.	43.8 mm
d <sub>b</sub> - min.	28.2 mm
r <sub>1,2</sub> min.	0.6 mm
Ball - D <sub>w</sub>	6.35 mm
r <sub>b</sub> - max.	0.3 mm
D <sub>b</sub> - max.	44.6 mm
Calculation factor f	1.05
Calculation factor e	0.68
d <sub>a</sub> - min.	28.2 mm
Calculation factor - f	1.05
r <sub>3,4</sub> - min.	0.3 mm
r <sub>1,2</sub> - min.	0.6 mm
Calculation factor - e	0.68
Ball diameter D <sub>w</sub>	6.35 mm
Basic dynamic load rating C	7.93 kN
Preload class A G <sub>A</sub>	70 N
Preload class B G <sub>B</sub>	210 N
Preload class C G <sub>C</sub>	430 N
Basic dynamic load rating - C	7.9 kN
Preload class B - G <sub>B</sub>	210 N
Preload class C - G <sub>C</sub>	430 N
Preload class A - G <sub>A</sub>	70 N
Fatigue load limit P <sub>u</sub>	0.166 kN
Calculation factor f <sub>1</sub>	0.99

Calculation factor $f_{2C}$	1.06
Calculation factor $f_{2B}$	1.03
Calculation factor $f_{HC}$	1
Calculation factor $f_{2A}$	1
Calculation factor - $f_1$	0.99
Limiting speed for oil lubrication	63000 mm/min
Fatigue load limit - $P_u$	0.166 kN
Calculation factor - $Y_0$	0.76
Calculation factor - $Y_1$	0.92
Calculation factor - $X_2$	0.67
Calculation factor - $Y_2$	1.41
Calculation factor - $f_{HC}$	1
Calculation factor - $f_{2C}$	1.06
Calculation factor - $f_{2B}$	1.03
Calculation factor - $f_{2A}$	1
Limiting speed for grease lubrication	42000 r/min
Basic static load rating $C_0$	3.9 kN
Static axial stiffness, preload class C	117 N/ $\mu$ m
Attainable speed for grease lubrication	42000 r/min
Static axial stiffness, preload class B	89 N/ $\mu$ m
Static axial stiffness, preload class A	59 N/ $\mu$ m
Attainable speed for oil-air lubrication	63000 r/min
Basic static load rating - $C_0$	3.9 kN
Reference grease	1.3 cm <sup>3</sup>

quantity $G_{ref}$	
Calculation factor (single, tandem) $Y_2$	0.87
Calculation factor (single, tandem) $Y_0$	0.38
Calculation factor (single, tandem) $X_2$	0.41
Calculation factor (back-to-back, face-to-face) $Y_1$	0.92
Calculation factor (back-to-back, face-to-face) $Y_2$	1.41
Calculation factor (back-to-back, face-to-face) $Y_0$	0.76
Calculation factor (back-to-back, face-to-face) $X_2$	0.67