



Bearing No. 30332

D	340 mm
d	160 mm
T	75 mm
B	68 mm
C	58 mm
a	64,6 mm
e	0.36
Cr	78000
Y0	0.92
db	205
da	187
Y1	1.7
B_	68
Sb	17
C0	960
Sa	10
D_	340
Z_	14
C_	58
C0r	98000
DA_	44.399
Iso	-
DE_	296.925
D_b	311
DI_	209.852
SBRG	3
SDM_	253.389
D_a2	293
KBRG	3111
yobi	30332

D_a1	322
mass	28.4
TC-RA	659.434
r min.	5 mm
Weight	28,4 Kg
TC-DA1	46.024
TC-DA2	42.773
TC-SLR	47
Da min	293 mm
LangID	1
ALPHA_	13.5
Db min.	311 mm
Oil rpm	1400
db max.	205 mm
Da max.	322 mm
ra max.	4 mm
hidYobi	30332
da min.	187 mm
T-ALP21	27
rb max.	3 mm
T-ALP22	0
T-ALP23	0
GRS rpm	1000
inner r	5
outer r	4
r1 min.	4 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	4
inner ra	4
outer rb	3
TC-BET22	0

Size (mm)	160x340x75
Width (mm)	75
Prod_Type3	TRBSR_MD_A
Bearing number	30332
Bore Diameter (mm)	160
Outer Diameter (mm)	340
Calculation factor (e)	0,36
Calculation factor (Y0)	0,92
(Oil) Lubrication Speed	1400 r/min
(Grease) Lubrication Speed	1000 r/min
Basic dynamic load rating (C)	765 kN
Basic static load rating (C0)	960 kN