



Bearing No. 30332D

D	340 mm
d	160 mm
T	75 mm
B	68 mm
C	48 mm
a	99,3 mm
e	0.81
Cr	69000
Y0	0.41
db	198
da	196
Y1	0.74
B_	68
Sb	27
C0	875
Sa	9
D_	340
Z_	15
C_	48
C0r	89000
DA_	41.579
Iso	-
DE_	286.062
D_b	313
DI_	208.493
SBRG	3
SDM_	247.278
D_a2	270
KBRG	3111
yobi	30332D

D_a1	322
mass	27.5
TC-RA	320.742
r min.	5 mm
Weight	27,5 Kg
TC-DA1	44.734
TC-DA2	38.424
TC-SLR	46
Da min	270 mm
LangID	1
ALPHA_	28.5
Db min.	313 mm
Oil rpm	1300
db max.	198 mm
Da max.	322 mm
ra max.	4 mm
hidYobi	30332D
da min.	196 mm
T-ALP21	57
rb max.	3 mm
T-ALP22	0
T-ALP23	0
GRS rpm	950
inner r	5
outer r	4
r1 min.	4 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	8
inner ra	4
outer rb	3
TC-BET22	0

Size (mm)	160x340x75
Width (mm)	75
Prod_Type3	TRBSR_MD_A
Bearing number	30332D
Bore Diameter (mm)	160
Outer Diameter (mm)	340
Calculation factor (e)	0,81
Calculation factor (Y0)	0,41
(Oil) Lubrication Speed	1300 r/min
(Grease) Lubrication Speed	950 r/min
Basic dynamic load rating (C)	675 kN
Basic static load rating (C0)	875 kN