



Bearing No. 30336

a	72,4 mm
e	0.36
d	180 mm
D	380 mm
T	83 mm
B	75 mm
C	64 mm
D_	380
C0	1230
Y0	0.92
B_	75
Y1	1.7
C_	64
Z_	15
Cr	95500
Sb	19
db	233
da	207
Sa	10
DA_	47.26
DI_	237.121
C0r	126000
DE_	329.365
D_b	345
Iso	-
yobi	30336
Noun	Bearing
KBRG	3111
mass	39.3
SDM_	283.243

SBRG	3
D_a1	362
Bore	7.087 Inch 180 Millimeter
D_a2	324
TC-RA	732.35
TC-SLR	52
LangID	1
Da min	324 mm
Weight	39,3 Kg
r min.	5 mm
UNSPSC	31171516
TC-DA2	45.535
ALPHA_	13.5
TC-DA1	48.985
T-ALP23	0
r1 min.	4 mm
GRS rpm	900
inner r	5
da min.	207 mm
outer r	4
T-ALP22	0
T-ALP21	27
rb max.	3 mm
Da max.	362 mm
hidYobi	30336
ra max.	4 mm
Db min.	345 mm
db max.	233 mm
Oil rpm	1300
hidTable	ecat_NSTPRM
inner ra	4
Category	Tapered Roller Bearings

	Assembly
TC-BET22	50
TC-BET21	3
TC-BET23	0
outer rb	3
Component	Assembly
Inventory	0.0
Size (mm)	180x380x83
Width (mm)	83
Prod_Type3	TRBSR_MD_A
cup width:	64 mm
cone width:	75 mm
Weight / LBS	86.642
Basic Number	30336
Product Group	B04334
Inch - Metric	Metric
Bearing number	30336
Other Features	Standard Angle Pressed Steel Cage
bore diameter:	180 mm
Assembly Width	3.268 Inch 83 Millimeter
Keyword String	Tapered
assembly type:	Cone & Cup
Precision Class	Standard
Outside Diameter	14.961 Inch 380 Millimeter
Manufacturer URL	http://www.nskamericas.com
Long Description	Assembly; Standard Precision; 180MM Bore; 380MM Outside Diameter; 83MM Assembly Width; Single Row of Rollers

Manufacturer Name	NSK
Weight / Kilogram	39.34
outside diameter:	380 mm
Bore Diameter (mm)	180
Outer Diameter (mm)	380
Minimum Buy Quantity	N/A
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Calculation factor (e)	0,36
Flange Outside Diameter	0 Inch 0 Millimeter
Calculation factor (Y0)	0,92
(Oil) Lubrication Speed	1300 r/min
Manufacturer Item Number	30336
manufacturer upc number:	029176068331
(Grease) Lubrication Speed	900 r/min
Basic static load rating (C0)	1230 kN
Basic dynamic load rating (C)	935 kN