

# sed Units Double Concentric Piloted Flange Cartridge | QAACW15A075S



Bearing No. QAACW15A075S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Metric                                                                                                                 |
| Bearing Number            | 4.67                                                                                                                   |
| Housing Construction      | 3.14                                                                                                                   |
| UPC Code                  | 22.00 lb10.00 Kg                                                                                                       |
| Shaft Size Type           | 0883450017404<br>0883450017411<br>0883450017435<br>0883450017442<br>0883450017459<br>0883450017466<br>0883450017473 08 |
| Full Timken Part Number   | 0.0020 in0.051 mm                                                                                                      |
| Locking Style             | 75 mm                                                                                                                  |
| Y2 - Geometry Factor      | 0.0020 in0.050 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0031 in0.080 mm                                                                                                      |
| Shaft Tolerance           | 2900 rpm                                                                                                               |
| Shaft Size                | 1600 rpm                                                                                                               |
| Pre Install Clearance Min | 1300 rpm                                                                                                               |
| Pre Install Clearance Max | Double Concentric                                                                                                      |