

loyal

Housed Units-Double Concentric Two-Bolt Pillow Block | QAAP18A304S



Bearing No. QAAP18A304S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.31                                                                                                                   |
| Housing Construction      | 2.90                                                                                                                   |
| UPC Code                  | 45 lb20.40 Kg                                                                                                          |
| Shaft Size Type           | 0883450319614<br>0883450319621<br>0883450319638<br>0883450319645<br>0883450319652<br>0883450319669<br>0883450319676 08 |
| Full Timken Part Number   | 0.0030 in0.076 mm                                                                                                      |
| Locking Style             | 3-1/4 in                                                                                                               |
| Y2 - Geometry Factor      | 0.0024 in0.060 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0039 in0.100 mm                                                                                                      |
| Shaft Tolerance           | 2400 rpm                                                                                                               |
| Shaft Size                | 1400 rpm                                                                                                               |
| Pre Install Clearance Min | 1000 rpm                                                                                                               |
| Pre Install Clearance Max | Double Concentric                                                                                                      |