

# Housed Units Double Concentric Two-Bolt Pillow Block | QAAPL15A212S



Bearing No. QAAPL15A212S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 4.67                                                                                                                   |
| Housing Construction      | 3.14                                                                                                                   |
| UPC Code                  | 28 lb12.7 Kg                                                                                                           |
| Shaft Size Type           | 0883450320931<br>0883450320948<br>0883450320955<br>0883450320962<br>0883450320979<br>0883450320986<br>0883450320993 08 |
| Full Timken Part Number   | 0.0020 in0.051 mm                                                                                                      |
| Locking Style             | 2-3/4 in                                                                                                               |
| Y2 - Geometry Factor      | 0.0020 in0.050 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0031 in0.080 mm                                                                                                      |
| Shaft Tolerance           | 2900 rpm                                                                                                               |
| Shaft Size                | 1600 rpm                                                                                                               |
| Pre Install Clearance Min | 1300 rpm                                                                                                               |
| Pre Install Clearance Max | Double Concentric                                                                                                      |